



## ZPMV2.E360653 Wiring, Printed - Component

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

### Wiring, Printed - Component

[See General Information for Wiring, Printed - Component](#)

#### ZENTRON (INTERNATIONAL) PCB LTD

E360653

Room 03, 14Th Fl, Blk A

Hi-Tech Industrial Centre

5-21 Pak Tin Par St

Tsuen Wan, N T, HONG KONG

Type	Cond Width		Cond	SS/ DS/	Max Area Diam	Solder		Max Oper Temp	Flame	Meets UL796	C
	Min	Edge				Thk	Limits				
	mm(in)	mm(in)	mic(mil)	DSO	mm(in)	C	sec	C	Class	DSR	I
<b>Mass-laminated printed wiring boards.</b>											
<b>2</b>	0.1 (0.004)	0.38 (0.015)	17 (0.67)	DS	76.2 (3.0)	260	10	130	V-0	All	*
<b>Multi-layer printed wiring boards.</b>											
<b>M</b>	0.15 (0.006)	0.46 (0.018)	17 (0.67)	DS	50.8 (2.0)	288	30	130	V-0	All	*
<b>Single layer printed wiring boards.</b>											
<b>1</b>	0.07 (0.003)	0.21 (0.008)	17 (0.67)	DS	76.2 (3.0)	288	20	130	V-0	▲	*
<b>11</b>	0.11 (0.004)	0.23 (0.009)	17 (0.67)	SS	76.2 (3.0)	260	10	105	V-0	All	*
<b>12</b>	0.11 (0.004)	0.23 (0.009)	17 (0.67)	SS	76.2 (3.0)	260	10	105	HB	-	*
<b>16</b>	0.1 (0.004)	0.23 (0.009)	34 (1.34)	SS	76.2 (3.0)	260	10	105	V-0	All	*
<b>18</b>	0.13 (0.005)	0.23 (0.009)	34 (1.34)	SS	76.2 (3.0)	260	10	105	HB	All	*
<b>19</b>	0.06 (0.002)	0.18 (0.007)	34 (1.34)	SS	50.8 (2.0)	260	10	130	V-0	All	*
<b>1A</b>	0.1 (0.004)	0.3 (0.012)	17 (0.67)	SS	76.2 (3.0)	260	10	130	V-0	All	*
<b>1B</b>	0.1 (0.004)	0.3 (0.012)	17 (0.67)	DS	38.1 (1.5)	260	10	130	V-0	All	*
<b>1C</b>	0.1 (0.004)	0.3 (0.012)	34 (1.34)	SS	50.8 (2.0)	260	10	130	V-0	All	*
<b>1D</b>	0.13 (0.005)	0.39 (0.015)	12 (0.47)	DS	50.8 (2.0)	288	10	130	V-0	All	*
<b>1F</b>	0.14 (0.006)	0.42 (0.017)	17 (0.67)	DS	76.2 (3.0)	288	20	130	V-0	All	*
<b>1H</b>	0.07 (0.003)	0.16 (0.006)	17 (0.67)	DS	76.2 (3.0)	288	20	130	V-0	All	*
<b>3</b>	0.05 (0.002)	0.15 (0.006)	17 (0.67)	DS	12.7 (0.5)	260	20	130	V-0	All	*
<b>4</b>	0.1 (0.004)	0.3 (0.012)	35 (1.38)	SS	38.1 (1.5)	260	10	130	V-0	All	*
<b>I1</b>	0.1 (0.004)	0.18 (0.007)	17 (0.67)	DS	76.2 (3.0)	260	10	130	V-0	All	*
<b>I1A</b>	0.1 (0.004)	0.18 (0.007)	17 (0.67)	SS	76.2 (3.0)	260	10	130	V-0	All	*
<b>I1B</b>	0.1 (0.004)	0.18 (0.007)	17 (0.67)	DS	38.1 (1.5)	260	10	130	V-0	All	*
<b>Single layer printed wiring boards, flammability only Recognition.</b>											
<b>18B</b>	0.06 (0.002)	0.18 (0.007)	34 (1.34)	SS	50.8 (2.0)	260	10	130	HB	All	*

\* - CTI PLC value marked on individual board

Marking: Company name or tradename "EGC" or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2014-06-30

---

[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

◆ 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".